


# Solatek TX-PA 30 KW



- Pure sine wave output
- Self-consumption and Feed-in to the grid
- Programmable supply priority for PV, Battery or Grid
- True galvanic isolation transformer design
- User-adjustable charging current
- Programmable multiple operation modes: Grid-tie, off-grid and grid-tie with backup
- Built-in timer for various mode on/off operation
- Multiple communication for USB, RS-232, Modbus and SNMP
- Monitoring software for real-time status display and control
- Parallel operation up to 4 units

## Solatek TX-PA 3 Phase Transformer Type Hybrid Inverter Specifications

MODEL	Solatek TX-PA 30KW
Maximum PV Input Power	45KW
Rated Output Power	30KW
Maximum Charging Power	30KW
<b>GRID-TIE OPERATION</b>	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 950 VDC
Start-up Voltage / Initial Feeding Voltage	500 VDC / 550 VDC
MPP Voltage Range	460 VDC ~ 900 VDC
Full power MPP Voltage Range	625 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	1 / 72A
GRID OUTPUT (AC)	
Nominal Output Voltage	230 VAC* (P-N) / 400 VAC (P-P)
Output Voltage Range	195.5 - 253 VAC per phase
Output Frequency Range	49 ~ 51 Hz or 59.3 ~ 60.5 Hz
Nominal Output Current	43.5 A per phase
Power Factor	1
EFFICIENCY	
Maximum Conversion Efficiency (DC/AC)	95%
<b>OFF-GRID OPERATION</b>	
AC INPUT	
AC Start-up Voltage/Auto Restart Voltage	150 - 170 VAC per phase / 180 VAC per phase
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	43.5 A per phase
PV INPUT (DC)	
Maximum DC Power / Maximum DC Voltage	45KW / 950 VDC
MPP Voltage Range	460 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	1 / 72 A
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Output Waveform	Pure Sinewave
Efficiency (DC to AC)	>91%
<b>HYBRID OPERATION</b>	
PV INPUT (DC)	
Nominal DC Voltage / Maximum DC Voltage	720 VDC / 950 VDC
Start-up Voltage / Initial Feeding Voltage	500 VDC / 550 VDC
MPP Voltage Range	460 VDC ~ 900 VDC
Number of MPP Trackers / Maximum Input Current	1 / 72 A
GRID OUTPUT (AC)	
Nominal Output Voltage	230 VAC* (P-N) / 400 VAC (P-P)
Output Voltage Range	195.5 - 253 VAC per phase
Output Frequency Range	49 ~ 51 Hz or 59.3 ~ 60.5 Hz
Nominal Output Current	43.5 A per phase
Power Factor	1
AC INPUT	
AC Start-up Voltage / Auto Restart Voltage	150 - 170 VAC per phase / 180 VAC per phase
Acceptable Input Voltage Range	170 - 280 VAC per phase
Maximum AC Input Current	43.5 A per phase
BATTERY MODE OUTPUT (AC)	
Nominal Output Voltage	230 VAC (P-N) / 400 VAC (P-P)
Efficiency (DC to AC)	>91%
<b>BATTERY &amp; CHARGER</b>	
Nominal Battery Voltage/Charging Voltage Range	384 VDC / 384 VDC ~ 480 VDC
Maximum Charging Current	80A
<b>GENERAL</b>	
<b>PHYSICAL</b>	
Dimension, D x W x H (mm)	430 x 715 x 1021
Net Weight (kgs)	223
<b>INTERFACE</b>	
Communication Port	RS-232/USB
Intelligent Slot	Optional SNMP, GPRS, WIFI, Modbus cards available
<b>ENVIRONMENT</b>	
Humidity	0 ~ 90% RH (Non-Condensing)
Operating Temperature	-10 to 55°C
Altitude	0 ~ 1000 m**

\*These figures are based on VDE-4105 standard. All figures may vary depending on different AC voltage and country requirements.

\*\*Power derating 1% every 100 m when altitude is over 1000 m.

Product specifications are subject to change without further notice.