

Solatek Fast Charging Station

SLTK-DCEV-(CCS2/GB-T)330

Solatek DC Fast charging station offers Electric Vehicle owners an opportunity to charge their car safely and quickly. A typical electric car with 95kWh battery pack could be charged up to 80% of its capacity in about 10minutes** (Depending on car's supported Charging protocol speed).

Solatek combines industry standardization with advanced charging technology to support next-generation electric vehicles. Its multi-protocol design allows for easy tailoring to support CHAdeMO, CCS1 & CCS2, Tesla, and GB/T for DC fast charging applications. Payment & billing platform solutions enable easy and secure payments via station payment terminals and RFID card.



High Voltage Charging Module

- Input voltage range: 380±15% VAC
- Output voltage range: 150~1000 VDC
- Output power: 330kW
- Fan intelligent speed regulation
- Fan failure detection alarm
- LED failure alarm

Main Features

- OCPP1.5 & OCPP1.6
- Galvanized cabinet
- Durable enclosure
- User friendly interface
- Built-in safety measures
- Flexible multi-protocol design
- Temperature range: -25°C to + 65°C
- Tesla, CHAdeMO, CCS, GB/T Protocol compatible
- Data management and metering options

Applications



Highways



Parking



Service
Station



Workplace



Fleet

Specifications

AC Nominal Input	
Phase	3 Phase + Neutral + PE
Voltage	380±15% VAC
Frequency	40 - 65 HZ (10%±)
DC Nominal Output	
Voltage	150 - 1000 VDC
Power	330KW (Constant Power)
Output Current	0 - 300 A
Electrical Parameter	
Power Factor	≥ 0.99
Unequal Current Radio	≤ 5%
Stable Voltage Accuracy	≤ ± 0.5%
Stable Current Accuracy	≤ ± 1%
Efficiency	≥ 95% max
Soft Start Time	3 - 8 s
Auxiliary Power	12 V
Structure Design	
Installation Method	Ground Mount
Charging Outlet	CCS2 +GBT
Cable Length	5 m (Standard)
LED Indicator	1 Indicator
LCD Screen	10 Inch Daylight Readable Touchscreen
Emergency Stop Button	Yes
Startup Mode	Plug-and-Play / RFID Card
RFID	Yes
Weights	≤ 450 kg
Dimensions (W x D x H)	90 x 78 x 190 cm
Communication	
EN-GATE vs. Charger	CAN 2.0 (CHAdEMO), CCS2,GBT
Network Connection	Ethernet, Wi-Fi, 3G, 4G
Communication Protocol	OCPP 1.5 / 1.6 (JSON)
Environmental Index	
Operating & Storage Temperature	-30°C to 65°C
Working Humidity	5% - 95% Without Condensation
Working Altitude	< 2000m
Protection Grade	IP54
Installation Environment	Indoor / Outdoor
Cooling Method	Fan Cooling (Liquid Cooling for Option)
Security Protection	
Multiple Protection	Over / Under Voltage Protection, Overload Protection, Short Circuit Protection Over / Under Temperature Protection, Surge Protection, Communication Failure
MTBF	1000,000 Hours

LED status indicator light

10 Inch/15 Inch Daylight Readable Touchscreen

Intelligent cable management design

